



MODEL:

AquaJet AJ-W-416L

AQUAJET



AquaJet Twin Mixer Tap with Lever control and 400mm Swivel Spout

Tap Hole Centres: 195-210mm adjustable

Accreditation: Kiwa KUKreg4 1+

Base: AJ-W-40

Connection(s): ½-inch

Controls: Lever

Model Range: AquaJet 40

Mount: Panel mounted

Pedestal: Twin Hole

Spout: 400mm swivel

Tap Type: Twin Mixer


Water Feed: Twin

FEATURES & BENEFITS

- Comprehensive range of taps manufactured to meet the rigours of commercial catering.
- High quality, robust construction specifically designed for commercial kitchens.
- Easy lever operation.
- Selection of spouts to suit most applications.
- Spare parts available.

TECHNICAL INFO

- Connection(s): ½-inch BSP female 195-210mm centres
- Height: 140mm
- Built-in non return valve
- Product material: nickel plated brass
- Product weight: 2.06kg
- Recommended working pressure: 1.5 - 5 bar
- Flow rates: 6.1 lpm tested at 3 bar pressure
- Certified to KUK Reg4 1+ by Kiwa
- Max recommended temperature 60°C



Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com