



MODEL:

**AquaJet AJPR10-ST-BF3-A****AQUAJET**

AquaJet Pre-Rinse Spray. AJPR10 base / STANDARD style / BF3 bowl filler / ANGLED gun

**Accreditation:** Kiwa KUKreg4 1+

**Base:** AJPR10

**Bowl Filler:** 400mm bowl filler (BF3)

**Connection(s):** (M) 1/2-inch

**Controls:** Lever

**Model Range:** AquaJet 10

**Mount:** Deck mounted

**Pedestal:** Single

**Spray Gun:** Angled

**Style:** Standard


**Water Feed:** Single Monobloc

#### FEATURES & BENEFITS

- A variety of choices to suit each application.
- Pre-assembled, ready to install - saves time on site.
- All assembled models are factory tested up to 6 bar for quality assurance.
- Choice of optional bowl fillers, water dispensing guns and accessories.
- Restraining device available to prevent hose from overstretching into basin, which reduces abuse and helps meet Water Board regulations.
- Super strong, food-grade, high-flow water hose.

#### TECHNICAL INFO

- Connection: 1/2-inch BSP male thread 50mm length
- Height: 1175mm
- Product weight: 5.04kg
- Recommended dynamic water pressure range: 1.5 - 5 bar. Max hot water temperature 60°C
- Product material: nickel plated brass, 304 stainless steel braided hose with EPDM lined inner hose
- Flow rates tested at 3 bar dynamic pressure: 7.75 l/m
- 1 year parts warranty
- Certified to KUK Reg4 1+ by Kiwa
- If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap.



Dimensions are in millimeters. If a Cad file is required please visit [www.mechline.com](http://www.mechline.com).



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: [info@mechline.com](mailto:info@mechline.com) | Web: [www.mechline.com](http://www.mechline.com)