

MODEL:

AquaJet AJPR20-ST-BF3-A



AquaJet Pre-Rinse Spray. AJPR20 base / STANDARD style / BF3 bowl filler / ANGLED gun

Accreditation: Kiwa KUKreg4 1+

Base: AJPR20

Bowl Filler: 400mm bowl filler (BF3) **Connection(s):** 2x (M) ½-inch

Controls: Lever

Model Range: AquaJet 20 Mount: Deck mounted Pedestal: Single Spray Gun: Angled Style: Standard


Water Feed: Twin Monobloc

FEATURES & BENEFITS

- A variety of choices to suit each application.
- Pre-assembled, ready to install saves time on site.
- All assembled models are factory tested up to 6 bar for quality assurance.
- Choice of optional bowl fillers, water dispensing guns and accessories.
- Restraining device available to prevent hose from overstretching into basin, which reduces abuse and helps meet Water Board regulations.
- Super strong, food-grade, high-flow water hose.

TECHNICAL INFO

- Connection: ½-inch BSP male thread x2 on brass yolk supplied allowing direct connection for hot and cold feeds
- Hole cut out requirement 30-35mm
- Height: 1175mm
- Product weight: 5.53kg
- Recommended dynamic water pressure range: 1.5 5 bar. Max hot water temperature 60°C
- Product material: nickel plated brass, 304 stainless steel braided hose with EPDM lined inner hose
- Flow rates tested at 3 bar dynamic pressure: 7.82 l/m Bowl Filler 5.97 l/m
- 1 year parts warranty
- Certified to KUK Reg4 1+ by Kiwa
- If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap.



Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.



MECHLINE DEVELOPMENTS LIMITED

2x (M) 1/2-inch connections
Tap hole req.: 30mm dia.

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com