

MODEL:

AquaJet AJPR40-ST-BF3-F



AquaJet Pre-Rinse Spray. AJPR40 base / STANDARD style / BF3 bowl filler / FAN BLADE gun

Tap Hole Centres: 195-210mm adjustable

Base: AJPR40

Bowl Filler: 400mm bowl filler (BF3)

Connection(s): 2x (F) ½-inch

Controls: Lever Model Range: Aqualet 40

Mount: Panel mounted Pedestal: Twin Spray Gun: Fan Blade Style: Standard Water Feed: Twin


FEATURES & BENEFITS

- A variety of choices to suit each application.
- Pre-assembled, ready to install saves time on site.
- All assembled models are factory tested up to 6 bar for quality assurance.
- Choice of optional bowl fillers, water dispensing guns and accessories.
- Restraining device available to prevent hose from overstretching into basin, which reduces abuse and helps meet Water Board regulations.
- Super strong, food-grade, high-flow water hose.

TECHNICAL INFO

- Connection: ½-inch BSP female adjustable inlets
- 2x 25-28mm hole cut out requirement with hole centres between 195-210mm
- Height: 1105mm
- Product weight 5.75kg
- Recommended dynamic water pressure range: 1.5 5 bar. Max hot water temperature 60°C
- Product material: nickel plated brass, 304 stainless steel braided hose with EPDM lined inner hose
- Flow rates tested at 3 bar dynamic pressure: 4 l/m bowl filler 6.05 l/m
- 1 year parts warranty
- If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap.





2x (F) 1/2-inch connections Tap hole req.: 2x 25mm dia.

Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com