



MODEL:

**AquaTechnix TX-B-116L**

# AQUATECHNIX



AquaTechnix LEVER operated faucet TX-B-10 base with 400mm swivel spout. H: 334mm

**Accreditation:** Kiwa KUKreg4 1+

**Base:** TX-B-10

**Connection(s):** ½-inch

**Controls:** Lever

**Model Range:** TX-10

**Mount:** Deck mounted

**Pedestal:** Single Hole

**Spout:** 400mm swivel

**Tap Type:** Monobloc

**Water Feed:** Single Monobloc

### FEATURES & BENEFITS

- Ergonomic in design and functionality.
- Modern, hygienic and practical design comes pre-assembled ready to install.
- All assembled models are factory tested up to 6 bar for quality assurance.
- Complete interchangeability between all bodies, spouts and pre-rinses means that product use can easily be changed on site at a later date.
- Includes PosiStop protected lever and dome heads for long life and reliability for all models

### TECHNICAL INFO

- Connection: ½-inch
- Height: 334mm
- Recommended static water pressure range: 1.5 - 5 bar
- Flow rates for all TX-B-10 models - tested at 3 bar pressure: Fitted with WATER-SAVING diffuser: 4.11 l/m (INCLUDED) Fitted with STANDARD diffuser: 10.84 l/m



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: [info@mechline.com](mailto:info@mechline.com) | Web: [www.mechline.com](http://www.mechline.com)