



MODEL:

AquaTechnix TX-PR-20L-SH-BFO

**AQUATECHNIX**


AquaTechnix Pre-Rinse Spray. LEVER operated TX-PR-20L base / SHORT height / No bowl filler H: 745mm

Accreditation: Kiwa KUKreg4 1+**Base:** TX-PR-20L**Bowl Filler:** No bowl filler (BFO)**Connection(s):** ½-inch copper tail**Controls:** Lever**Height:** Short**Model Range:** TX-20**Mount:** Deck mounted**Pedestal:** Single**Water Feed:** Twin Monobloc**FEATURES & BENEFITS**

- Ergonomic in design and functionality
- Modern, hygienic and practical design comes pre-assembled ready to install.
- All assembled models are factory tested up to 6 bar for quality assurance.
- Complete interchangeability between all bodies, spouts and pre-rinses means that product use can easily be changed on site at a later date.
- Includes PosiStop protected lever and dome heads for long life and reliability for all models and Brass Back Nuts
- Choice of height and bowl filler available
- Built in check valve for backflow protection
- Water saving options for spray gun and bowl filling spout included

TECHNICAL INFO

- Connection: ½-inch male BSP to ½-inch compression
- Hole cut out requirement 32-38mm
- Height: 745mm
- Product weight: 3.45kg
- Recommended dynamic water pressure range: 1.5 - 5 bar. Max hot water temperature 60°C
- Flow rates for all TX-PR-20 models - tested at 3 bar dynamic pressure: SPRAY GUN WATER-SAVING face plate: 4.65 l/m. SPRAY GUN STANDARD face plate: 7.75 l/m. BOWL FILLER WATER-SAVING diffuser: 3.56 l/m. BOWL FILLER STANDARD diffuser: 10.33 l/m.
- 2 year parts warranty
- Certified to KUK Reg4 1+ by Kiwa
- If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap
- Requires a balanced supply of hot and cold water with a difference no greater than 1 bar at the inlets

Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.MECHLINE DEVELOPMENTS LIMITED
Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com