



MODEL:

**AquaTechnix TX-W-15DJ18D****AQUATECHNIX**

AquaTechnix DOME head operated faucet TX-W-15 base with 450mm double jointed spout. H: 376mm

**Accreditation:** Kiwa KUKreg4 1+

**Base:** TX-W-15

**Connection(s):** ½-inch

**Controls:** Dome

**Model Range:** TX-15

**Mount:** Panel mounted

**Pedestal:** Single Hole

**Spout:** 450mm double jointed

**Tap Type:** Monobloc


**Water Feed:** Single Monobloc

#### FEATURES & BENEFITS

- Ergonomic in design and functionality.
- Modern, hygienic and practical design comes pre-assembled ready to install.
- All assembled models are factory tested up to 6 bar for quality assurance.
- Complete interchangeability between all bodies, spouts and pre-rinses means that product use can easily be changed on site at a later date.
- Includes PosiStop protected lever and dome heads for long life and reliability for all models

#### TECHNICAL INFO

- Connection: ½-inch. 30mm maximum wall/panel thickness
- Height: 376mm
- Recommended static water pressure range: 1.5 - 5 bar
- Flow rates for all TX-W-15 models - tested at 3 bar pressure:  
Fitted with WATER-SAVING diffuser: 3.70 l/m (INCLUDED) Fitted with STANDARD diffuser: 10.31 l/m



Dimensions are in millimeters. If a Cad file is required please visit [www.mechline.com](http://www.mechline.com).



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: [info@mechline.com](mailto:info@mechline.com) | Web: [www.mechline.com](http://www.mechline.com)