

MODEL:

BaSix BSX-MHB-HCW-T

BASIX



BaSix Mobile Hand Wash Station. Designed to help operations meet their requirements to provide hand-wash facilities for staff and customers on site. The BSX-MHB-HCW-T model is ideal for areas where a hot and cold water supply and waste connection are present.

Mobile: Yes


Controls: Hands-Free

FEATURES & BENEFITS


- UK manufactured
- Time flow foot valve operated
- Thermostatic mixer valve supplied
- Large foot void of 245 x 180mm - for ease of operation
- Spout fitted with water-saving diffuser
- Low flow rate of 0.6lpm with water-saving diffuser as supplied (tested at 3 bar pressure)
- An extremely small footprint of only 384 x 360mm
- High grade polished 304 stainless steel for the bowl and corrosion resistant 430 for the main body
- Reinforced, heavy-duty stainless steel foot plate
- Splashback - to protect walls from water splashes
- Front hinged door, with ¼ turn thumb latch, to access services and supplied internal lower storage shelf
- 2x castors and splashback grab handle allows simple transportation
- Castors can be removed to allow flush to wall fitting if desired

TECHNICAL INFO


- SITE REQUIREMENTS: Hot and cold water (min. 1.5 bar) and waste connection (1 ¼ inch)
- WEIGHT: 15.6 kg (without optional soap dispenser)
- Main construction material 304 grade stainless steel
- Supplied with thermostatic mixing valve for hot & cold supplies with integrally fitted check valves



SIDE VIEW



FRONT VIEW



BOWL

Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com