



MODEL:

CaterConnex (Gas) C-GR038

CATERCONNEX



Compact Gas Regulators/Governors

Connection(s): []-inch

FEATURES & BENEFITS

- For use with natural gas or LPG commercial catering equipment - can be installed vertically or horizontally.
- Gas Port Size: []-inch
- Housing Material: Aluminium, cast iron [RV 131]
- Internal Components: Steel, aluminium, elastomer
- Mounting: Suitable for multi-positional mounting. Install with gas flowing as indicated by the arrow on bottom casting

TECHNICAL INFO

- Pipe Sizes: Rp []-in
- Pemax/pimax mbar: 100
- Porange mbar: 2.5 - 30
- Construction and Design: According to EN 88 and Gas Appliances Directive 90/396/EEC
- Classification: Regulator grade B, group 2 according to EN 88
- Gas type: gas family 1, 2 and 3 according to EN 437
- Inlet Pressure: 100 mbar
- Outlet Pressure: 2.5 to 30 mbar (standard pressure is Orange @ 10-20 mbar)
- Thread Connections: According to ISO 7-1, EN 10226-1 and DIN 2999 part 1



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com