MODEL: **Delabie DLB-2211**

DELABIE



Delabie □-inch Single Lever Mixer tap with swivelling spout and retractable spray head


Connection(s): ½-inch
Controls: Lever
Mount: Deck mounted
Pedestal: Single Hole
Spout: Swivel
Tap Type: Monobloc Mixer
Water Feed: Twin

FEATURES & BENEFITS

- Spray head can pull out and extend to approximately 1-metre.
- Ergo control lever.
- Retracting hand spray with 2 jet options: flow straightener/rain effect.
- Body with smooth interior.
- Mixed water brass outlet L. 105mm.
- Counterweight specific to flexible hose.
- Chrome-plated brass body and Hygiene control lever.
- No manual contact thanks to hygiene control lever.
- PEX flexibles F□-inch supplied and reinforced fixing via 2 stainless steel rods.

TECHNICAL INFO

- Connection(s): F□-inch.
- Drop height: 105mm.
- Spout length: 200mm.
- Ceramic cartridge with pre-set max temperature limiter
- Flow rate: 7 lpm
- Product material: Chrome plated brass
- Max recommended temperature 60°C



Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.

MECHLINE DEVELOPMENTS LIMITED
Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com

©2019 All rights reserved. All material on these pages, including and without limitation text, logos, icons, photographs and all other artwork, is copyright material of Mechline Developments Ltd, unless otherwise stated. Commercial use of this material may only be made with the express, prior, written permission of Mechline. This includes material provided by any third party, including material obtained through links to other sites from Mechline's pages or its af liates and commercial associates. Material and information included are correct at time of print. Intending buyers and users must satisfy themselves as to the suitability and safety of the products for their particular purposes and duties. Dimensions shown in mm unless otherwise stated. Product accreditation may not apply to all products in the relevant range. Please contact Mechline to con rm. Unless otherwise stated, all products carry a warranty of twelve (12) months against manufacturing defect or workmanship on parts with no inclusion for labour or site attendance.