



MODEL:

Delabie DLB-758ENC

DELABIE

BINOPTIC Cross wall electronic basin mixer. L 20mm spout for recessed installation, M 3/8-inch fittings


Accreditation: WRAS
Controls: Mains supply
Mount: Panel mounted
Tap Type: Binoptic

FEATURES & BENEFITS

- Independent IP65 electronic control unit.
- 230/12V mains supply with transformer.
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
- Scale resistant flow straightener.
- Adjustable duty flush (pre-set flush ~60 sec. every 24hr after last use).
- Active, infrared presence detection, sensor at the end of the spout optimises detection.
- Filters and solenoid valves.
- Chrome-plated brass body and spout.
- Anti-blocking safety.
- Spout with smooth interior and low volume of water (reduces bacterial niches).
- Mixer valves can be fitted, if required.

TECHNICAL INFO

- Connection(s): M 3/8-inch.
- Spout length: 200mm.
- Flow rate: 3 lpm.



Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com