

MODEL:

Delabie DLB-98001230

DELABIE

Deck mounted TEMPOMATIC 4 electronic mixer tap

Controls: Battery operated **Mount:** Deck mounted **Tap Type:** Tempomatic 4


FEATURES & BENEFITS

- Battery-operated with integrated 123 6V Lithium batteries
- Water savings up to 90 %
- Total hygiene : no manual contact
- Anti-bacterial proliferation duty flush (~60 seconds every 24 hours after last use).
- Reduced-stagnation solenoid valve and electronic unit integrated into the body of the mixer
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 6 lpm
- Scale-resistant flow straightener
- Active, infrared presence detection, sensor at the end of the spout optimises detection
- Chrome-plated stainless steel body
- Cap fixed in place by 2 concealed screws
- PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves
- Fixing reinforced by two stainless steel rods
- Anti-blocking security
- Side temperature control with long lever and adjustable maximum temperature limiter.

TECHNICAL INFO

- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.4 6 lpm.
- PEX flexibles Ø 15mm for compression fittings with stopcocks, filters and non-return valves
- Total height: 150mm
- Product material: Chrome plated stainless steel body
- Battery operated supplied with 6v 123 lithium batteries
- WRAS approved
- Product weight: 1.02kg





Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com