



MODEL:

Dormont 2650NPVF36KM 768720
BS 669-2:1997**Dormont**
A WATTS Brand

Dormont UNBRAIDED ½-inch 1000mm Gas Hose “NPVF” + Quick-Disconnect Coupling + Straight Restrainer Cable with mounting hardware

Connection(s): ½-inch**Accreditation:** BS669-2:1997**Accreditation:** BSI Kitemark (KM 768720)**Hose Length:** 1000mm**Hose Type:** Unbraided "NPVF"**FEATURES & BENEFITS**

- Dormont gas hoses are of the highest quality and reliability with safety features built in.
- Fit & Forget saving time and money.
- Designed with safety and long-life in mind.
- Approved for both gas families: LPG & Natural Gas.
- Push-to-connect, Flat-Faced Quick Disconnect Coupling.
- Designed for catering applications.
- 304 Stainless Steel, Helically formed hose - flexible and strong.
- Flared-end Mechanical fittings - for strength & reliability.
- All Hoses Annealed - to increase flexibility & corrosion resistance.
- PVC dipped coating - wrinkle free, easy to clean & durable.
- Antimicrobial coating - to resist build up of bacteria for hygiene.
- Full assembly and product testing carried out by Mechline, U.K.

TECHNICAL INFO

- Length: 1000mm
- Connection Size: ½-inch
- Hose BTU Flow Rating at 0.55 sp. Gr. Natural Gas, 0.58mbar Pressure Drop, 37.96 MJ/m³ - 66000
- Flow rating BTU @ 0.22sp LPG-Propane gas 0.58mbar pressure drop, 95MJ/m³ - 165000
- Flow rating BTU @ 0.17sp LPG-Butane gas 0.58mbar pressure drop, 121MJ/m³ - 165000



MECHLINE DEVELOPMENTS LIMITED

Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com