MODEL: **Dormont 2650NPVF362S**



Dormont UNBRAIDED ½-inch 1000mm Gas Hose “NPVF” + Quick-Disconnect Coupling + 2 SwivelMax + Straight Restrainer Cable with mounting hardware

Accreditation: BS669-2:1997
Connection(s): ½-inch
Hose Length: 1000mm
Hose Type: Unbraided "NPVF"

FEATURES & BENEFITS

- SwivelMAX provides unique multi-plane rotational movement to increase aisle space in the kitchen; decreases stress on the hose and thereby increase the service life of the hose. Maximise performance, mobility, space & safety. Can be fitted to standard or braided gas hoses as part of the original assembly. Cannot be retro-fitted.
- Dormont gas hoses are of the highest quality and reliability with safety features built in.
- Fit & Forget saving time and money.
- Designed with safety and long-life in mind.
- Approved for both gas families: LPG & Natural Gas.
- Push-to-connect, Flat-Faced Quick Disconnect Coupling.
- Designed for catering applications.
- 304 Stainless Steel, Helically formed hose - flexible and strong.
- Flared-end Mechanical fittings - for strength & reliability.
- All Hoses Annealed - to increase flexibility & corrosion resistance.
- PVC dipped coating - wrinkle free, easy to clean & durable.
- Antimicrobial coating - to resist build up of bacteria for hygiene.
- Full assembly and product testing carried out by Mechline, U.K.

TECHNICAL INFO

- Length: 1000mm
- Connection Size: ½-inch
- Hose BTU Flow Rating at 0.55 sp. Gr. Natural Gas, 0.58mbar Pressure Drop, 37.96 MJ/m³ - 66000
- Flow rating BTU @ 0.22sp LPG-Propane gas 0.58mbar pressure drop, 95MJ/m³ - 165000
- Flow rating BTU @0.17sp LPG-Butane gas 0.58mbar pressure drop, 121MJ/m³ - 165000

MECHLINE DEVELOPMENTS LIMITED
Tel: +44 (0)1908 261511 | Email: info@mechline.com | Web: www.mechline.com

©2019 All rights reserved. All material on these pages, including and without limitation text, logos, icons, photographs and all other artwork, is copyright material of Mechline Developments Ltd, unless otherwise stated. Commercial use of this material may only be made with the express, prior, written permission of Mechline. This includes material provided by any third party, including material obtained through links to other sites from Mechline’s pages or its af liates and commercial associates. Material and information included are correct at time of print. Intending buyers and users must satisfy themselves as to the suitability and safety of the products for their particular purposes and duties. Dimensions shown in mm unless otherwise stated. Product accreditation may not apply to all products in the relevant range. Please contact Mechline to con rm. Unless otherwise stated, all products carry a warranty of twelve (12) months against manufacturing defect or workmanship on parts with no inclusion for labour or site attendance.