



Certificate number: 2306733-01 (1)

Issued 16/06/2023
Expires N/A 1+

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Mechline Developments Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)(a) of the Water Supply (Water Fittings) Regulations 1999 England & Wales:
2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Mechline Developments Ltd. ,
ONE Brudenell Drive,
Brinklow,
Milton Keynes,
MK10 0DE, United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2306733-01

The following products belong to this certificate

Product: Range of basin / sink taps with chrome plated brass bodies. Fitted with ceramic disc headworks. ATS1+ With Production Surveillance.description:
Models: TX-500BL - 1/2-inch Basin Taps (pair) H: 130mm – lever handle TX-500BD - 1/2-inch Basin Taps (pair) H: 130mm – dome handle TX-500SL - 1/2-inch Sink Taps (pair). H: 172mm – lever handle TX-500SD - 1/2-inch Sink Taps (pair). H: 172mm – dome handle
Size: ½" BSP(M)
Scope: Manufacturer recommended maximum working pressure 5 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.
Marking: Operating member moulded 'M'
Materials: Non-metallic materials assessed (BS6920) to point of discharge.
Backflow protection notes: If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel (for example, a sink or washbasin), a Type AUK3 air gap is achieved which permits installation of the tap in any premises where backflow protection up to Fluid Category 5 is required at the tap.
Additional notes: All water contact & exposed components satisfy opacity requirements.

Extra Notes: