



Certificate number: 2306725-01 (1)

Issued 15/06/2023
Expires N/A 1+

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)
Model number(s) – see Appendix

Mechline Developments Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)(a) of the Water Supply (Water Fittings) Regulations 1999 England & Wales:
2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Mechline Developments Ltd.,
ONE Brudenell Drive,
Brinklow,
Milton Keynes,
MK10 0DE,
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2306725-01

The following products belong to this certificate

Product description: Range of commercial kitchen taps and pre-rinse taps with various assembly options depending on model variant and which can include a spring loaded pull down trigger operated spray rinse handset and or swivel spout outlet. The bodies are chrome plated brass and depending on model can be: twin pedestal, twin feed and deck mounted / twin pedestal, twin feed, panel mounted / single pedestal, single feed deck mounted or single pedestal, twin feed deck mounted / single pedestal, single feed, panel mounted body.

Please refer to model for a full range of options.

ATS1+ With Production Surveillance.

Models:

TX-W-40(-E) body taps dome/lever

TX-W-4VVVX(-E)

X:

D – dome handle

L – lever handle

VVV:

SG6 – 150mm swivel gooseneck spout – TXSG6SPOUT

06 – 150mm swivel spout - TXSP150SPOUT

06F – 150mm flat swivel spout - TXSP150FSPOUT

08F – 200mm low profile spout - TXSP200FSPOUT

12 – 300mm swivel spout - TXSP300SPOUT

12F - 300mm flat swivel spout - TXSP300FSPOUT

16 – 400mm swivel spout - TXSP400SPOUT

DJ18 – 450mm double jointed spout - TXSP450DJSPOUT

(-E) – this code addition specifies the use of the TX-W-40-E version of the body adapted to the European market which is 30mm shorter than the UK market body.

TX-W-40(-E) body pre rinses dome/lever

TX-PR-40X-YY-ZZZ(-E)

X:

D – dome handle

L – lever handle

YY:

SS – SUPER SHORT:

• BF0: 200mm riser tube and 460mm hose

• BF1/2: 120mm riser tube and 460mm hose

SH – SHORT: 350mm riser tube and 600mm hose

ST – STANDARD: 500mm riser tube and 930mm hose

BFZ:

BF0 – no bowl filler

BF1 – 150mm bowl filling faucet - TXSP150FSPOUT

BF2 – 300mm bowl filling faucet - TXSP300FSPOUT

(-E) – this code addition specifies the use of the TX-W-40-E version of the body adapted to the European market which is 30mm shorter than the UK market body.

TX-B-30 body taps dome/lever.

TX-B-30-E body taps dome/lever.

TX-B-3VVVX(-E)

X:

D – dome handle.

L – lever handle.

VVV:

SG6 – 150mm swivel gooseneck spout - TXSG6SPOUT

06 – 150mm swivel spout - TXSP150SPOUT

06F – 150mm flat swivel spout - TXSP150FSPOUT

Product Certificate

Appendix to Certificate number: 2306725-01

08F – 200mm low profile spout - TXSP200FSPOUT
12 – 300mm swivel spout - TXSP300SPOUT
12F - 300mm flat swivel spout - TXSP300FSPOUT
16 – 400mm swivel spout - TXSP400SPOUT
DJ18 – 450mm double jointed spout - TXSP450DJSPOUT
(-E) – this code addition specifies the use of the TX-B-30-E version of the body adapted to the European market which is 30mm shorter than the UK market body.

TX-B-30 body pre rinses dome/lever.
TX-B-30-E body pre rinses dome/lever.
TX-PR-30X-YY-BFZ(-E)

X:

D – dome handle.

L – lever handle.

YY:

SS – SUPER SHORT:

• BF0: 200mm riser tube and 460mm hose.

• BF1/2: 120mm riser tube and 460mm hose.

SH – SHORT: 350mm riser tube and 600mm hose.

ST – STANDARD: 500mm riser tube and 930mm hose.

BFZ:

BF0 – no bowl filler.

BF1 – 150mm bowl filling faucet - TXSP150FSPOUT

BF2 – 300mm bowl filling faucet - TXSP300FSPOUT

(-E) – this code addition specifies the use of the TX-B-30-E version of the body adapted to the European market which is 30mm shorter than the UK market body.

TX-B-10 body taps dome/lever

TX-B-20 body taps dome/lever

TX-B-20-E body taps dome/lever

TX-B-1VVVX

TX-B-2VVVX(-E)

X:

D – dome handle

L – lever handle

VVV:

SG6 – 150mm swivel gooseneck spout - TXSG6SPOUT

06 – 150mm swivel spout - TXSP150SPOUT

06F – 150mm flat swivel spout - TXSP150FSPOUT

08F – 200mm low profile spout - TXSP200FSPOUT

12 – 300mm swivel spout - TXSP300SPOUT

12F - 300mm flat swivel spout - TXSP300FSPOUT

16 – 400mm swivel spout - TXSP400SPOUT

DJ18 – 450mm double jointed spout - TXSP450DJSPOUT

(-E) – this code addition specifies the use of the TX-B-20-E version of the body adapted to the European market which uses 100mm connectors for flexible hoses rather than copper tails.

TX-B-10 body pre rinses dome/lever

TX-B-20 body pre rinses dome/lever

TX-B-20-E body pre rinses dome/lever

TX-PR-10X-YY-BFZ

TX-PR-20X-YY-BFZ(-E)

X:

D – dome handle

L – lever handle

YY:

Product Certificate

Appendix to Certificate number: 2306725-01

SS – SUPER SHORT:

- BF0: 200mm riser tube and 460mm hose
- BF1/2: 120mm riser tube and 460mm hose

SH – SHORT: 350mm riser tube and 600mm hose

ST – STANDARD: 500mm riser tube and 930mm hose

BFZ:

BF0 – no bowl filler

BF1 – 150mm bowl filling faucet - TXSP150FSPOUT

BF2 – 300mm bowl filling faucet - TXSP300FSPOUT

BF3 – 400mm bowl filling faucet - TXSP400SPOUT

(-E) – this code addition specifies the use of the TX-B-20-E version of the body adapted to the European market which uses 100mm connectors for flexible hoses rather than copper tails.

TX-W-15 body taps dome/lever

TX-W-15VVVX

X:

D – dome handle

L – lever handle

VVV:

SG6 – 150mm swivel gooseneck spout - TXSG6SPOUT

06 – 150mm swivel spout - TXSP150SPOUT

06F – 150mm flat swivel spout - TXSP150FSPOUT

08F – 200mm low profile spout - TXSP200FSPOUT

12 – 300mm swivel spout - TXSP300SPOUT

12F - 300mm flat swivel spout - TXSP300FSPOUT

16 – 400mm swivel spout - TXSP400SPOUT

DJ18 – 450mm double jointed spout - TXSP450DJSPOUT

TX-W-15 body pre rinses dome/lever

TX-PR-15X-YY-BFZ

X:

D – dome handle

L – lever handle

YY:

SS – SUPER SHORT:

- BF0: 200mm riser tube and 460mm hose
- BF1/2: 120mm riser tube and 460mm hose

SH – SHORT: 350mm riser tube and 600mm hose

ST – STANDARD: 500mm riser tube and 930mm hose

BFZ:

BF0 – no bowl filler

BF1 – 150mm bowl filling faucet - TXSP150FSPOUT

BF2 – 300mm bowl filling faucet - TXSP300FSPOUT

Size:

1/2" BSP(M)

Scope:

Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 60°C.

Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.

Marking:

Operating member moulded M.

Materials:

Non-metallic materials assessed (BS6920) to point of discharge.

Backflow protection notes:

Consideration must be made on installation to the airgap arrangement.

Additional notes:

Product Certificate

Appendix to Certificate number: 2306725-01

All water contact & exposed components satisfy opacity requirements.

Extra Notes: