

MODEL:

CaterConnex F06



CATERCONNEX

Stainless Steel Braided Tap Hose

Connections: 1/2-inch x 15mm

Hose type: Braided tap hose

Hose length: 300mm

Bore size: 10mm

Accreditation: WRAS

FEATURES & BENEFITS

- Braided tap hose c/w push fit and isolation valve
- Water hoses for commercial catering applications.
- WRAS approved.
- APPLICATION: For hot and cold water, to sanitary fittings, pumps, catering equipment, air-conditioning, sink taps, heating or between rigid pipework.
- FITTINGS: Crimped (swaged) ferrules in Nickel-Plated Brass; end fittings are Brass, Chrome Plated or Plastic.
- Fittings can be either male or female, push fit, elbow or straight.
- Other fittings are available on request as special order.

TECHNICAL INFO

- Bore dia. OD mm: 14.
- Connections: 1/2-inch x 15mm.
- Working pressure (Bar): 15.
- Bend radius mm: 40.

MAINTENANCE & CLEANING

Cleaning chrome: Do not use abrasive, chlorine or acid-based cleaning products. Avoid contact with concentrated bleach. Clean with soapy water using a cloth or sponge.

Dimensions are in millimeters. If a Cad file is required please visit www.mechline.com.